



# Certificate of Compliance

Certificate Number: DL-2019113739C

**Applicant:** **Shenzhen Starmax Technology Co., Ltd**  
J405-406 Jinhetian Business Center, 329 Longhuan San Rd., Sanlian Community, Longhua District, Shenzhen, China

**Manufacturer:** **Shenzhen Starmax Technology Co., Ltd**  
J405-406 Jinhetian Business Center, 329 Longhuan San Rd., Sanlian Community, Longhua District, Shenzhen, China

**Product:** **Smart Bracelet**

**M/N:** **S5**  
**S10, XS10, S20, S30, S40, S50, S60, S70, S80**

Essential requirement		Applied Specifications/Standards	Documentary Evidence
Art.3.1(a)	Safety	EN 62368-1:2014+A11:2017	DL-2019113739R
Art.3.1(a)	Health	EN 62479:2010	DL-2019113740R
Art.3.1(b)	EMC	ETSI EN 301 489-1 V2.2.1 (2019-03) ETSI EN 301 489-17 V3.2.0 (2017-03) EN 55032:2015; EN 55032:2017	DL-2019113741R
Art.3.2	Radio	ETSI EN 300 328 V2.2.1 (2019-04)	DL-2019113742R

The EUT described above has been tested by us with the listed standards and found in compliance with the council Radio Equipment Directive (RED) 2014/53/EU. It is possible to use CE marking to demonstrate the compliance with this RE Directive. It is only valid in connection with the test report number: DL-2019113739R/ DL-2019113740R/ DL-2019113741R/ DL-2019113742R



This certificate of conformity is based on a single evaluation of the submitted sample(s) of the above mentioned product. It does not imply an assessment of the whole product and relevant. Without the written approval, It is not permitted to use the test lab's logo.

Shenzhen DL Testing Technology Co., Ltd.  
Part One of 301, A-2 Factory Building, Yalijia Industrial Plant, No. 87, Hengping Road, Yuanshan Street, Longgang District, Shenzhen, China

Web: [www.dl-cert.com](http://www.dl-cert.com) E-mail: [Service@dl-cert.com](mailto:Service@dl-cert.com) Tel: 400-688-3552



*Registered / Eingetragen 25/03/2021*

*No 008472690-0001*



**EUROPEAN UNION INTELLECTUAL  
PROPERTY OFFICE  
CERTIFICATE OF REGISTRATION**

This Certificate of Registration is hereby issued for the Registered Community Design identified below. The corresponding entries have been recorded in the Register of Community Designs.

---

**AMT DER EUROPÄISCHEN UNION FÜR  
GEISTIGES EIGENTUM  
EINTRAGUNGSRURKUNDE**

Diese Eintragungsurkunde wird für das unten genannte eingetragene Gemeinschaftsgeschmacksmuster ausgestellt. Die entsprechenden Einträge sind in das Register für Gemeinschaftsgeschmacksmuster aufgenommen worden.

*The Executive Director / Der  
Exekutivdirektor*


*Christian Archambeau*






21 008472690-0001  
25 EN - DE  
22 25/03/2021  
15 25/03/2021  
45 29/03/2021  
11 008472690-0001  
72 Zhongtao Han  
73 Zhongtao Han  
208A  
Floor 2  
Property A1  
West Plaza  
Shenzhen North Railway Station  
Zhiyuan Middle Road  
Longhua District, Shenzhen, Guangdong 518000  
REPÚBLICA POPULAR DE CHINA  
74 Thomas B. Ruhland  
Friedrichstr. 94  
D-10117 Berlin  
ALEMANIA  
51 10 - 02  
54 BG - Смарт часовници  
ES - Relojes inteligentes  
CS - Chytré hodinky  
DA - Smarture  
DE - Smartwatches  
ET - Nutikellad  
EL - Έξυπνα ρολόγια χειρός  
EN - Smartwatches  
FR - Montres intelligentes  
IT - Orologi intelligenti  
LV - Viedie rokaspulksteņi  
LT - Išmanieji rankiniai laikrodžiai  
HR - Pametni ručni satovi  
HU - Okosórák  
MT - Arloġġi tal-idejn tat-tip smart  
NL - Smartwatches  
PL - Zegarki inteligentne  
PT - Relógios de pulso inteligentes  
RO - Ceasuri inteligente  
SK - Inteligentné hodinky  
SL - Pametne zapestne ure  
FI - Älykellot  
SV - Smarta klockor


30 -  
55



0001.1



0001.2



0001.3



0001.4



0001.5



0001.6



0001.7



# **FCC TEST REPORT**

**Test report  
On Behalf of  
Shenzhen Starmax Technology Co., Ltd  
For  
Smart Bracelet  
Model No.: S5, S10, XS10, S20, S30, S40, S50, S60, S70, S80  
FCC ID:2ASAU-S5**

**Prepared for :** Shenzhen Starmax Technology Co., Ltd  
J405-406 Jinhedian Business Center, 329 Longhuan San Rd., Sanlian Community,  
Longhua District, Shenzhen, China

**Prepared By :** Shenzhen HUAKE Testing Technology Co., Ltd.  
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street,  
Bao'an District, Shenzhen City, China

**Date of Test:** Nov. 16, 2019 ~Nov. 22, 2019

**Date of Report:** Nov. 22, 2019

**Report Number:** HK1911222984-E





## TEST RESULT CERTIFICATION

**Applicant's name** ..... : Shenzhen Starmax Technology Co.,Ltd  
**Address** ..... : J405-406 Jinhetian Business Center, 329 Longhuan San Rd.,  
Sanlian Community, Longhua District, Shenzhen, China  
**Manufacture's Name** ..... : Shenzhen Xinyiheng Digital Co., Ltd.  
**Address** ..... : 4/Floor 3/Building, Baishun Industrial Zone, Makan Village, Xili  
Town, Nanshan District, Shenzhen City, China  
**Product description**  
Trade Mark: N/A  
Product name ..... : Smart Bracelet  
Model and/or type reference : S5, S10, XS10, S20, S30, S40, S50, S60, S70, S80  
**Standards** ..... : FCC Rules and Regulations Part 15 Subpart C Section 15.249  
ANSI C63.10: 2013

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAKE Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAKE Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Date of Test** ..... :  
Date (s) of performance of tests ..... : Nov. 16, 2019 ~Nov. 22, 2019  
Date of Issue ..... : Nov. 22, 2019  
Test Result ..... : **Pass**

Testing Engineer : Gary Qian  
(Gary Qian)  
Technical Manager : Eden Hu  
(Eden Hu)  
Authorized Signatory : Jason Zhou  
(Jason Zhou)



<b>Table of Contents</b>	<b>Page</b>
1 . TEST SUMMARY	4
2 . GENERAL INFORMATION	5
2.1 GENERAL DESCRIPTION OF EUT	5
2.2 Carrier Frequency of Channels	6
2.3 Operation of EUT during testing	6
2.4 DESCRIPTION OF TEST SETUP	6
2.5 MEASUREMENT INSTRUMENTS LIST	7
3 . CONDUCTED EMISSIONS TEST	8
3.1 Conducted Power Line Emission Limit	8
3.2 Test Setup	8
3.3 Test Procedure	8
3.4 Test Result	9
4 RADIATED EMISSION TEST	11
4.1 Radiation Limit	11
4.2 Test Setup	11
4.3 Test Procedure	12
4.4 Test Result	12
5 BAND EDGE	18
5.1 Limits	18
5.2 Test Procedure	18
5.3 Test Result	19
6 OCCUPIED BANDWIDTH MEASUREMENT	21
6.1 Test Setup	21
6.2 Test Procedure	21
6.3 Measurement Equipment Used	21
6.4 Test Result	21
7 ANTENNA REQUIREMENT	23
8 PHOTOGRAPH OF TEST	24
8.1 Radiated Emission	24
8.2 Conducted Emission	25
9 PHOTOS OF THE EUT	26



## 1. TEST SUMMARY

### 1.1 TEST PROCEDURES AND RESULTS

DESCRIPTION OF TEST	RESULT
CONDUCTED EMISSIONS TEST	COMPLIANT
RADIATED EMISSION TEST	COMPLIANT
BAND EDGE	COMPLIANT
OCCUPIED BANDWIDTH MEASUREMENT	COMPLIANT
ANTENNA REQUIREMENT	COMPLIANT

### 1.2 TEST FACILITY

Test Firm : Shenzhen HUAKE Testing Technology Co., Ltd.

Address : 1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street, Bao'an District, Shenzhen City, China

### 1.3 MEASUREMENT UNCERTAINTY

Measurement Uncertainty	
Conducted Emission Expanded Uncertainty	= 2.23dB, k=2
Radiated emission expanded uncertainty(9kHz-30MHz)	= 3.08dB, k=2
Radiated emission expanded uncertainty(30MHz-1000MHz)	= 4.42dB, k=2
Radiated emission expanded uncertainty(Above 1GHz)	= 4.06dB, k=2



## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

Equipment	Smart Bracelet
Model Name	S5
Serial Model	S10, XS10, S20, S30, S40, S50, S60, S70, S80
Model Difference	All model's the function, software and electric circuit are the same, only with a product color and model named different. Test sample model: S5
FCC ID	2ASAU-S5
Antenna Type	Internal Antenna
Antenna Gain	0dBi
BT Operation frequency	2402-2480MHz
Number of Channels	40CH
Modulation Type	GFSK
Power Source	DC 3.7V From Battery or DC5V From USB
Power Rating	DC 3.7V From Battery or DC5V From USB



## 2.2 Carrier Frequency of Channels

Channel List							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2402	11	2422	21	2442	31	2462
02	2404	12	2424	22	2444	32	2464
03	2406	13	2426	23	2446	33	2466
04	2408	14	2428	24	2448	34	2468
05	2410	15	2430	25	2450	35	2470
06	2412	16	2432	26	2452	36	2472
07	2414	17	2434	27	2454	37	2474
08	2416	18	2436	28	2456	38	2476
09	2418	19	2438	29	2458	39	2478
10	2420	20	2440	30	2460	40	2480

## 2.3 Operation of EUT during testing

### Operating Mode

The mode is used: **Transmitting mode**


Low Channel: 2402MHz

Middle Channel: 2440MHz

High Channel: 2480MHz

## 2.4 DESCRIPTION OF TEST SETUP

Operation of EUT during testing:



- PC information  
Model: TP00067A  
Input: DC20V, 2.25-3.25A  
Output: 5VDC, 0.5A

The sample was placed (0.8m below 1GHz, 1.5m above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. The worst case is X position



## 2.5 MEASUREMENT INSTRUMENTS LIST

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	R&S	ENV216	HKE-002	Dec. 27, 2018	1 Year
2.	Receiver	R&S	ESCI 7	HKE-010	Dec. 27, 2018	1 Year
3.	RF automatic control unit	Tonscend	JS0806-2	HKE-060	Dec. 27, 2018	1 Year
4.	Spectrum analyzer	R&S	FSP40	HKE-025	Dec. 27, 2018	1 Year
5.	Spectrum analyzer	Agilent	N9020A	HKE-048	Dec. 27, 2018	1 Year
6.	Preamplifier	Schwarzbeck	BBV 9743	HKE-006	Dec. 27, 2018	1 Year
7.	EMI Test Receiver	Rohde & Schwarz	ESCI 7	HKE-010	Dec. 27, 2018	1 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	HKE-012	Dec. 27, 2018	1 Year
9.	Loop Antenna	Schwarzbeck	FMZB 1519 B	HKE-014	Dec. 27, 2018	1 Year
10.	Horn Antenna	Schwarzbeck	9120D	HKE-013	Dec. 27, 2018	1 Year
11.	Pre-amplifier	EMCI	EMC051845 SE	HKE-015	Dec. 27, 2018	1 Year
12.	Pre-amplifier	Agilent	83051A	HKE-016	Dec. 27, 2018	1 Year
13.	EMI Test Software EZ-EMC	Tonscend	JY3120-B Version	HKE-083	Dec. 27, 2018	N/A
14.	Power Sensor	Agilent	E9300A	HKE-086	Dec. 27, 2018	1 Year
15.	Spectrum analyzer	Agilent	N9020A	HKE-048	Dec. 27, 2018	1 Year
16.	Signal generator	Agilent	N5182A	HKE-029	Dec. 27, 2018	1 Year
17.	Signal Generator	Agilent	83630A	HKE-028	Dec. 27, 2018	1 Year
18.	Shielded room	Shiel Hong	4*3*3	HKE-039	Dec. 27, 2018	3 Year
19.	Horn Antenna	Schwarzbeck	BBHA 9170	HKE-017	Dec. 27, 2018	1 Year



### 3. CONDUCTED EMISSIONS TEST


#### 3.1 Conducted Power Line Emission Limit

For intentional device, according to § 15.207(a) Line Conducted Emission Limits is as following

Frequency (MHz)	Maximum RF Line Voltage (dB $\mu$ V)			
	CLASS A		CLASS B	
	Q.P.	Ave.	Q.P.	Ave.
0.15 - 0.50	79	66	66-56*	56-46*
0.50 - 5.00	73	60	56	46
5.00 - 30.0	73	60	60	50

\* Decreasing linearly with the logarithm of the frequency

#### 3.2 Test Setup



#### 3.3 Test Procedure

- 1, The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10.
- 2, Support equipment, if needed, was placed as per ANSI C63.10.
- 3, All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4, If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5, All support equipments received AC power from a second LISN, if any.
- 6, The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7, Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.




### 3.4 Test Result

PASS

All the test modes completed for test. only the worst result of of (GFSK High Channel ) was reported as below:

Test Specification: Line



Suspected List				
NO.	Freq. [MHz]	Factor [dB]	Margin [dB]	Detector
1	0.1860	10.05	2.14	PK
2	0.1995	10.03	6.71	AV
3	0.2940	10.03	12.46	AV
4	0.2940	10.03	8.47	PK
5	0.3930	10.04	11.65	PK
6	0.3975	10.04	15.60	AV
7	0.5730	10.05	12.69	PK
8	0.6315	10.05	15.03	AV
9	0.9420	10.06	16.29	AV
10	1.0590	10.07	16.16	PK
11	4.6275	10.26	11.11	PK
12	4.6590	10.26	16.61	AV

Remark: Margin = Limit – Level


Correction factor = Cable lose + LISN insertion loss

Level=Test receiver reading + correction factor





Test Specification: Neutral



Suspected List				
NO.	Freq. [MHz]	Factor [dB]	Margin [dB]	Detector
1	0.1950	10.03	3.40	PK
2	0.1950	10.03	5.35	AV
3	0.3030	10.04	13.28	AV
4	0.3030	10.04	7.94	PK
5	0.3930	10.04	14.78	AV
6	0.4110	10.03	13.22	PK
7	1.5315	10.11	17.36	AV
8	1.7025	10.13	14.83	PK
9	4.3665	10.25	6.18	PK
10	4.8165	10.26	15.28	AV
11	6.3825	10.22	18.18	PK
12	7.5885	10.17	23.22	AV

Remark: Margin = Limit – Level

Correction factor = Cable lose + LISN insertion loss

Level=Test receiver reading + correction factor



## 4 RADIATED EMISSION TEST

### 4.1 Radiation Limit

For intentional device, according to § 15.209(a), the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500


§15.249(a) The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
2400-2483.5 MHz	50	500


§15.249(e) – As shown in §15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

### 4.2 Test Setup


#### (1) Radiated Emission Test-Up Frequency Below 30MHz



#### (2) Radiated Emission Test-Up Frequency 30MHz~1GHz



### (3) Radiated Emission Test-Up Frequency Above 1GHz



### 4.3 Test Procedure

1. Below 1GHz measurement the EUT is placed on turntable which is 0.8m above ground plane. And above 1GHz measurement EUT was placed on low permittivity and low tangent turn table which is 1.5m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The test frequency range from 9KHz to 25GHz per FCC PART 15.33(a).

#### Note:

For battery operated equipment, the equipment tests shall be performed using a new battery.

### 4.4 Test Result


#### PASS

All the test modes completed for test. The worst case of Radiated Emission is CH 2402; the test data of this mode was reported.



Below 1GHz Test Results:

Antenna polarity: H



#### Suspected List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	51.3400	18.05	-13.85	40.00	21.95	100	34	Horizontal
2	101.780	16.77	-15.41	43.50	26.73	100	133	Horizontal
3	167.740	21.27	-17.51	43.50	22.23	100	293	Horizontal
4	239.520	29.80	-13.88	46.00	16.20	100	284	Horizontal
5	345.250	31.08	-11.67	46.00	14.92	100	165	Horizontal
6	800.180	37.95	-3.12	46.00	8.05	100	149	Horizontal


Remark: Margin = Limit – Level

Correction factor = Cable lose + LISN insertion loss

Level=Test receiver reading + correction factor



Antenna polarity: V



#### Suspected List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	62.0100	24.61	-15.66	40.00	15.39	100	115	Vertical
2	89.1700	18.39	-17.27	43.50	25.11	100	215	Vertical
3	108.570	17.86	-15.43	43.50	25.64	100	12	Vertical
4	157.070	20.80	-18.43	43.50	22.70	100	12	Vertical
5	296.750	25.79	-12.77	46.00	20.21	100	54	Vertical
6	400.540	28.50	-10.40	46.00	17.50	100	12	Vertical

Remark:

Margin = Limit – Level

Level=Test receiver reading + factor

Factor= Antenna factor + cable loss- Amp factor

#### Harmonics and Spurious Emissions

##### Frequency Range (9 kHz-30MHz)

Frequency (MHz)	Level@3m (dBμV/m)	Limit@3m (dBμV/m)
--	--	--
--	--	--
--	--	--
--	--	--

**Note:**1. Emission Level=Reading+ Cable loss+ Antenna factor-Amp factor

2. The emission levels are 20 dB below the limit value, which are not reported. It is deemed to comply with the requirement

Above 1 GHz Test Results:  
CH Low (2402MHz)

Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2402	109.36	-5.84	103.52	114	-10.48	peak
2402	86.02	-5.84	80.18	94	-13.82	AVG
4804	57.15	-3.64	53.51	74	-20.49	peak
4804	43.39	-3.64	39.75	54	-14.25	AVG
7206	55.08	-0.95	54.13	74	-19.87	peak
7206	41.28	-0.95	40.33	54	-13.67	AVG
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2402	111.74	-5.84	105.9	114	-8.1	peak
2402	83.63	-5.84	77.79	94	-16.21	AVG
4804	54.02	-3.64	50.38	74	-23.62	peak
4804	45.56	-3.64	41.92	54	-12.08	AVG
7206	52.16	-0.95	51.21	74	-22.79	peak
7206	38.22	-0.95	37.27	54	-16.73	AVG
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

## CH Middle (2440MHz)

Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2440	108.14	-5.71	102.43	114	-11.57	peak
2440	80.66	-5.71	74.95	94	-19.05	AVG
4880	50.23	-3.51	46.72	74	-27.28	peak
4880	42.58	-3.51	39.07	54	-14.93	AVG
7320	52.46	-0.82	51.64	74	-22.36	peak
7320	38.96	-0.82	38.14	54	-15.86	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2440	104.12	-5.71	98.41	114	-15.59	peak
2440	84.63	-5.71	78.92	94	-15.08	AVG
4880	55.08	-3.51	51.57	74	-22.43	peak
4880	43.69	-3.51	40.18	54	-13.82	AVG
7320	52.15	-0.82	51.33	74	-22.67	peak
7320	40.56	-0.82	39.74	54	-14.26	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



## CH High (2480MHz)

Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2480	105.74	-5.65	100.09	114	-13.91	peak
2480	82.56	-5.65	76.91	94	-17.09	AVG
4960	52.08	-3.43	48.65	74	-25.35	peak
4960	41.36	-3.43	37.93	54	-16.07	AVG
7440	53.15	-0.75	52.4	74	-21.6	peak
7440	36.73	-0.75	35.98	54	-18.02	AVG
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2480	105.36	-5.65	99.71	114	-14.29	peak
2480	82.06	-5.65	76.41	94	-17.59	AVG
4960	52.13	-3.43	48.7	74	-25.3	peak
4960	44.52	-3.43	41.09	54	-12.91	AVG
7440	55.28	-0.75	54.53	74	-19.47	peak
7440	37.16	-0.75	36.41	54	-17.59	AVG
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Remark :

- (1) Measuring frequencies from 1 GHz to the 25 GHz.
- (2) "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency.
- (3) \* denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- (4) Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for peak measurement with peak detector at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average measurement with peak detection at frequency above 1GHz.
- (6) When the test results of Peak Detected below the limits of Average Detected, the Average Detected is not need completed. For example: Top Channel at Fundamental 73.16dBuV/m(PK Value) <93.98(AV Limit), at harmonic 53.20 dBuV/m(PK Value) <54 dBuV/m(AV Limit), the Average Detected not need to completed.
- (7) All modes of operation were investigated and the worst-case emissions are reported.





## 5 BAND EDGE

### 5.1 Limits

FCC PART 15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

### 5.2 Test Procedure

The band edge compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW to 100KHz and VBM to 300KHz to measure the peak field strength and set RBW to 1MHz and VBW to 10Hz to measure the average radiated field strength. The conducted RF band edge was measured by using a spectrum analyzer. Set span wide enough to capture the highest in-band emission and the emission at the band edge. Set RBW to 100 KHz and VBW to 300 KHz, to measure the conducted peak band edge.



**PASS**

Horizontal (Worst case)

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2310	55.16	-5.81	49.35	74	-24.65	peak
2310	/	-5.81	/	54	/	AVG
2390	52.86	-5.84	47.02	74	-26.98	peak
2390	/	-5.84	/	54	/	AVG
2400	55.13	-5.84	49.29	74	-24.71	peak
2400	/	-5.84	/	54	/	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.





## 6 OCCUPIED BANDWIDTH MEASUREMENT

### 6.1 Test Setup

Same as Radiated Emission Measurement

### 6.2 Test Procedure

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Set EUT as normal operation.
3. Based on ANSI C63.10 section 6.9.2: RBW= 30KHz. VBW= 100 KHz, Span=4MHz.
4. The useful radiated emission from the EUT was detected by the spectrum analyser with peak detector.

### 6.3 Measurement Equipment Used


Same as Radiated Emission Measurement

### 6.4 Test Result

**PASS**


Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.189	<b>PASS</b>
2440 MHz	1.132	<b>PASS</b>
2480 MHz	1.134	<b>PASS</b>

CH: 2402MHz





CH: 2440MHz



CH: 2480MHz



## 7 ANTENNA REQUIREMENT


### Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### Antenna Connected Construction

The antenna used in this product is a Internal Antenna, The directional gains of antenna used for transmitting is 0dBi.


### ANTENNA





## 8 PHOTOGRAPH OF TEST

### 8.1 Radiated Emission





## 8.2 Conducted Emission







## 9 PHOTOS OF THE EUT

Reference to the reporter : ANNEX A of external photos and ANNEX B of internal photos

-----End of test report-----

## CERTIFICATE of Conformity

**EC Council Directive 2014/35/EU**

**Certificate No.: XK2103032092C**

**Applicant** : **Shenzhen Starmax Technology Co.,Ltd**  
J405-406, 4th Floor, Jinhetian Industry Park Qingquan Rd., Longhua,  
Shenzhen

**Manufacturer** : **Shenzhen Starmax Technology Co.,Ltd**  
J405-406, 4th Floor, Jinhetian Industry Park Qingquan Rd., Longhua,  
Shenzhen

**Product** : **Smart bracelet**

**Test Model** : **S50,S60, S80, S90, S100**

**Brand Name** : **N/A**

**Test Standard** : **EN 60529:1991+A1:2000+A2:2013**

The certificate of conformity is based on an evaluation of a sample of the above mentioned product. Technical report is at the applicant disposal. This is to certify the tested sample that is in conformity with all provisions of above LVD directive. It is only valid in connection with the test report number XK2103032092S

The certificate does not imply the assessment of the production and does not permit using the SiCT's logo without permission.

# IP68

Authorized Signer: \_\_\_\_\_

Jesse Lin/Manager

Date: March 3, 2021



**Shenzhen SiCT Technology Co., Ltd.**

4F, Building A, EDerH Industrial District, Fukang Community, Longhua

Subdistrict, Longhua District, Shenzhen, Guangdong, P. R. China

E-mail: [info@sict-lab.com.cn](mailto:info@sict-lab.com.cn) Http:// [www.sict-lab.com.cn](http://www.sict-lab.com.cn)



# Certificate of Compliance

Certificate Number: DL-2019113743C

**Applicant:** Shenzhen Starmax Technology Co., Ltd  
J405-406 Jinhetian Business Center, 329 Longhuan San Rd., Sanlian Community, Longhua District, Shenzhen, China

**Manufacturer:** Shenzhen Starmax Technology Co., Ltd  
J405-406 Jinhetian Business Center, 329 Longhuan San Rd., Sanlian Community, Longhua District, Shenzhen, China

**Product:** Smart Bracelet

**M/N:** S5  
S10, XS10, S20, S30, S40, S50, S60, S70, S80

**Test Standard:** IEC62321-1:2013

The EUT described above has been consolidated by us and found in compliance with the council RoHS directive 2011/65/EU its amendment Directive EU 2015/863. It is possible to use RoHS marking to demonstrate the compliance with this RoHS Directive. It is only valid in connection with the test report number: DL-2019113743R.

# RoHS



This certificate of conformity is based on a single evaluation of the submitted sample(s) of the above mentioned product. It does not imply an assessment of the whole product and relevant. Without the written approval, It is not permitted to use the test lab's logo.

Shenzhen DL Testing Technology Co., Ltd.  
Part One of 301, A-2 Factory Building, Yalijia Industrial Plant, No. 87, Hengping Road, Yuanshan Street, Longgang District, Shenzhen, China

Web: [www.dl-cert.com](http://www.dl-cert.com) E-mail: [Service@dl-cert.com](mailto:Service@dl-cert.com) Tel: 400-688-3552

